

INDUSTRIAL COMPONENT DATA

SACC-DSI-FS-5CON-L180/SH BU 1457940 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-FS-5CON-L180/SH BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-FS-5CON-L180/SH BU
Catalog number	1457940
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-1F854F2EE7
Generated	2026-08-04

Product Overview

Flush-type connector

Conect. plug. to be apar. wall poster., 5-pole, Connecting female, straight, M12-SPEEDCON, A-coded, Rear mount, M16 x 1.5, Soldering pins, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) 1239852

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1457940

Packing unit 20 pc

Minimum order quantity 20 pc

Note Made to Order (non-returnable)

Catalog page Page 62 (PC-2011)

GTIN 4046356632706

Weight per Piece (excluding packing) 14.530 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length of the solder pin 6 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder pins

Mounting type Rear mounting M16 x 1.5 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, nickel-plated

Sealing material FKM

Cable

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-FS-5CON-L180/SH BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.