


INDUSTRIAL COMPONENT DATA

SACC-DSI-M 8MS-6CON-M 8/0,5 1453494 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M 8MS-6CON-M 8/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M 8MS-6CON-M 8/0,5
Catalog number	1453494
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-D011939E13
Generated	2026-08-01

Product Overview

Flush-type connector

Conect. plug. to be apar. wall poster., 6-pole, Male connector, straight, M8, Rear mounting, M8 x 1, Single stranded wires, cable length: 0.5 m, 0.14 mm², PVC conductor

Device connector rear mounting, 6-position, Pin, straight, M8, Rear mounting, M8 x 1, Individual wires, cable length: 0.5 m, 0.14 mm², PVC litz wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataMountingMounting type Rear mounting M8 x 1 With flat nut

Assembly note With flat nut

Product propertiesProduct type Circular connectors (device side)

Number of positions 6

No. of cable outlets 1

Shielded no

Coding A

Thread type M8

Data management status

Article revision 02

Insulation characteristics

Overvoltage category II
Degree of pollution 3
Material specifications Flammability rating according to UL 94 HB
Seal material FKM
Contact material Cu alloy
Contact surface material Au
Contact carrier material PUR/PA 6.6
Material for screw connection Brass, nickel-plated
Conductor material Tin-plated Cu litz wires
Electrical properties Rated surge voltage 0.8 kV
Contact resistance $\leq 3 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current $I_N 1.5 \text{ A}$
Max. conductor resistance $80 \text{ }\Omega/\text{km}$
Connection data Conductor connection
Connection method Individual wires
Contact connection type Pin
Conductor cross section 0.14 mm^2
Tightening torque 1 Nm ... 1.5 Nm (Installation-side)
Connector Connection 1
Head design Pin
Head cable outlet straight
Head thread type M8
Cable/line Cable length 0.5 m
Cable type PVC litz wire
Wire diameter incl. insulation $1.3 \text{ mm} \pm 0.1 \text{ mm}$
Single wire, color black, brown, blue, white, gray, pink
Cable cross section 0.14 mm^2
Conductor material Tin-plated Cu litz wires
Conductor structure signal line 7x 0.16 mm
AWG signal line 24
Material wire insulation PVC / UL
Thickness, insulation 0.38 mm
Nominal voltage, cable 300 V
Test voltage, ca...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M 8MS-6CON-M 8/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.