

INDUSTRIAL COMPONENT DATA

SACC-DSI-MS-5CON-M12-SCO SH 1552968 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-MS-5CON-M12-SCO SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-MS-5CON-M12-SCO SH
Catalog number	1552968
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-DEB22F4559
Generated	2026-08-03

Product Overview

Panel feed-through

Conect. plug. to be apar. poster wall, 5-pole, Male connector, straight, M12-SPEEDCON, coding: A, Rear mounting, M12 x 1, Soldering pins, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240021
Rear device connector, 5-pin, Connector, straight, M12-SPEEDCON, code: A, Rear mounting, M12 x 1, Shanks, Alternative according to RoHS II without exception 6c (Pb < 0.1 %) Item no.: 1240021

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1552968

Packing unit 20 pc

Minimum order quantity 20 pc

Catalog page Page 188 (C-2-2013)

GTIN 4046356161992

Weight per Piece (excluding packing) 8.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 60 V

Rated surge voltage 1.5 kV

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder pins

Insertion/withdrawal cycles > 100

Torque 1.5 Nm ... 2 Nm (Installation-side)

Mounting type Rear mounting M12 x 1 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-MS-5CON-M12-SCO SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.