


INDUSTRIAL COMPONENT DATA

SACC-DSIV-M12MS-5CON-L180 SH 1437193 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSIV-M12MS-5CON-L180 SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSIV-M12MS-5CON-L180 SH
Catalog number	1437193
Category	Circular connector, mounting (PCB)
Minimum order	10 Pcs
Document ID	EO-B45182C05B
Generated	2026-08-01

Product Overview

Flush-type connector

Built-in mounting plug for sensors/actuators, 5-pole, M12, shielded, A-coded, backwall mount/bolt-on mount, with M12 thread, torsion-protected, with straight weld connection

Sensor-actuator flush-mounted plug, 5-pin, M12, shielded, A-coded, rear/screw mount with M12 thread, with torsion protection, straight solder connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1437193

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 262 (C-2-2013)

GTIN 4046356460378

Weight per Piece (excluding packing) 8.710 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 60 V

Rated surge voltage 1.5 kV

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder pins

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Rear mounting M12 x 1 With locking nut

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Nickel-plated brass

Sealing material NBR

Cable

Standards/specifications M12 connector IEC 61076-2-101

Ambient temperature (operation) -40 °C....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSIV-M12MS-5CON-L180 SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.