

INDUSTRIAL COMPONENT DATA

SACCBP-MS-5CON-PG9/1,0-920SCO 1437575 PHOENIX CONTACT Bus system flush-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-MS-5CON-PG9/1,0-920SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-MS-5CON-PG9/1,0-920SCO
Catalog number	1437575
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-1A865C862A
Generated	2026-07-31

Product Overview

Bus system flush-type plug

Conect. plug. to be apar. poster wall, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, lilac red RAL 4001, shielded, Male, straight, M12-SPEEDCON, coding: A, free cable end, Rear mounting, Cable connection, cable length: 1 m, CANopen®/DeviceNet™, PUR, violet, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239663

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1437575

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 427 (C-2-2017)

GTIN 4046356457705

Weight per Piece (excluding packing) 81.600 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 1 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 60 V

Rated surge voltage 1.5 kV

Number of positions 5

Insulation resistance 100 MΩ

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Signal type/category DeviceNet™

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles > 100

Torque 2 Nm ... 3 Nm (Installation-side)

Material

Flammability rating according to UL 94 V0

Sealing material FKM

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Cable

Cable type CAN Bus/DeviceNet

Cable type (abbreviation) 920

UL AWM style 21198 (80°C/300 V)

Signal type/category CANopen®

DeviceNet™

Cable structure 2xAWG24/19+2xAWG22/19

Conductor cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-MS-5CON-PG9/1,0-920SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.