

INDUSTRIAL COMPONENT DATA

SACCBP-MS-8CON-M16/2,0-PUR SCO 1419438 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-MS-8CON-M16/2,0-PUR SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-MS-8CON-M16/2,0-PUR SCO
Catalog number	1419438
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-D0A3205B47
Generated	2026-08-03

Product Overview

Flush-type connector

Conect. plug. to be apar. poster wall, Universal, 8-pole, halogen-free PUR, grayish black RAL 7021, shielded, Male connector, straight, M12-SPEEDCON, coding: A, at free cable end, Rear mounting, M16 x 1.5, Cable connection, cable length: 2 m, 0.25 mm², halogen-free PUR black, Alternative product according to RoHS II without exception 6c (Pb < 0.1%) item code: 1239257

Rear device connector, universal, 8-pin, halogen-free, grey-black RAL 7021, shielded, Connector, straight, M12-SPEEDCON, coding: A, on free conductor end, rear-mounted, M16 x 1.5, Cable connection, cable length: 2 m, 0.25 mm², halogen-free PUR black, Alternative according to RoHS II without exception 6c (Pb < 0.1 %) Item no.: 1239257

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1419438

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 46 (C-2-2017)

GTIN 4046356533348

Weight per Piece (excluding packing) 131.700 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 2 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 2 A

Rated voltage 30 V

Rated surge voltage 0.8 kV

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Rear mounting M16 x 1.5 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, nickel-plated

Sealing material FKM

Cable

Cable type PUR halogen-free black

Cable abbreviation Li9Y-V1-C-V1-11Y

Conductor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-MS-8CON-M16/2,0-PUR SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.