

INDUSTRIAL COMPONENT DATA

SP 4/15 3043734 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SP 4/15



Manufacturer	PHOENIX CONTACT
MPN / Reference	SP 4/15
Catalog number	3043734
Category	Terminal block connector
Minimum order	10 Pcs
Document ID	EO-40D113B78B
Generated	2026-07-29

Product Overview

Plug

Connector, rated voltage: 800 V, rated current: 32 A, number of poles: 15, connection type: Spring connection, Sizing cross-section: 4 mm², cross-section: 0.08 mm²- 6 mm², color: gray

Plug, nom. voltage: 800 V, nominal current: 32 A, number of positions: 15, connection method: Spring-cage connection, Rated cross section: 4 mm², cross section: 0.08 mm²- 6 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Terminal plug

Number of positions 15

Pitch 6.2 mm

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 8 kV

Connection dataNominal cross section 4 mm²

Stripping length 8 mm ... 10 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 61984

Conductor cross section rigid 0.08 mm² ... 6 mm²

Cross section AWG 28 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.08 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 28 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 4 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Nominal current 32 A

Maximum load current 32 A (with 6 mm² conductor cross section)

Nominal voltage 800 V

Nominal cross section 4 mm²

Dimensions Width 93 mm

Height 21 mm

Depth 41.5 mm

Length 21 mm

Pitch 6.2 mm

Material specifications Color gray (RAL 7042)

Flammability rating according to UL 94 V0

Insulating material group I

Insulating material PA

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SP 4/15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.