

INDUSTRIAL COMPONENT DATA

SP 4/ 3 3042900 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SP 4/ 3



Manufacturer	PHOENIX CONTACT
MPN / Reference	SP 4/ 3
Catalog number	3042900
Category	Terminal block connector
Minimum order	50 Pcs
Document ID	EO-6259CED30B
Generated	2026-07-29

Product Overview

Plug

Connector, rated voltage: 800 V, rated current: 32 A, number of poles: 3, connection type: Spring connection, Sizing cross-section: 4 mm², cross-section: 0.08 mm²- 6 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3042900

Packing unit 50 pc

Catalog page Page 333 (C-1-2017)

GTIN 4017918956257

Weight per Piece (excluding packing) 13.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 3

Number of levels 1

Number of connections 3

Nominal cross section 4 mm²

Color gray

Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Maximum load current 32 A (with 6 mm² conductor cross section)
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Maximum load current 32 A (with 6 mm² conductor cross section)
Nominal current I_N 32 A
Nominal voltage U_N 800 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SP 4/ 3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.