


INDUSTRIAL COMPONENT DATA

SP-H 2,5/11 3210716 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SP-H 2,5/11



Manufacturer	PHOENIX CONTACT
MPN / Reference	SP-H 2,5/11
Catalog number	3210716
Category	Terminal block connector
Minimum order	10 Pcs
Document ID	EO-189CEFC0C5
Generated	2026-07-28

Product Overview

Plug

Connector, rated voltage: 500 V, rated current: 24 A, number of poles: 11, connection type: Spring connection, Sizing cross-section: 2.5 mm², cross-section: 0.08 mm²- 4 mm², color: gray

Plug, nom. voltage: 500 V, nominal current: 24 A, number of positions: 11, connection method: Spring-cage connection, Rated cross section: 2.5 mm², cross section: 0.08 mm²- 4 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Terminal plug

Number of positions 11

Pitch 5.2 mm

Potentials 1

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 6 kV

Connection dataNominal cross section 2.5 mm²

Stripping length 8 mm ... 10 mm

Internal cylindrical gage A3
Connection in acc. with standard IEC 61984
Conductor cross section rigid 0.08 mm² ... 4 mm²
Cross section AWG 28 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.08 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 28 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²
Nominal current 24 A
Maximum load current 24 A (with 4 mm² conductor cross section)
Nominal voltage 500 V
Nominal cross section 2.5 mm²
Dimensions Width 57.2 mm
Height 15.8 mm
Depth 39 mm
Length 15.8 mm
Pitch 5.2 mm
Material specifications Color gray (RAL 7042)
Flammability rating according to UL 94 V0
Insulating material group I
Insulating material PA
Static insulating material application in cold -60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rai...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SP-H 2,5/11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.