


INDUSTRIAL COMPONENT DATA

PML-T108 (52X560)R CUS 1014264 PHOENIX CONTACT

Pipeline markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-T108 (52X560)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-T108 (52X560)R CUS
Catalog number	1014264
Category	Warning/signing plate
Minimum order	1 Pcs
Document ID	EO-0B4F953979
Generated	2026-08-04

Product Overview

Pipeline markers

Pipe marker, available: by lines, brown/red, labeled according to customer specifications: Flammable liquids, mounting class: glued, diameter: 0 mm, usable surface: 52 x 560 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1014264

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 345 (C-5-2013)

GTIN 4046356784702

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 52 mm

Width (a) 560 mm

Height (c) 52 mm

Diameter 0.00 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color brown/red

Type Rectangle

Components Silicone-free

Material Polyester

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing flammable liquids

Number of individual labels per row 1

Adhesive Acrylic

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Procedure

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Procedure A

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Adhesive strength 46 µm

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 10.0.140200202eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027371301eCl@ss 5.127371300eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-T108 (52X560)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.