

INDUSTRIAL COMPONENT DATA

WP-PA HF 10,0 BK 3240680 PHOENIX CONTACT Protective hose

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-PA HF 10,0 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WP-PA HF 10,0 BK
Catalog number	3240680
Category	Protective plastic hose
Minimum order	50 Pcs
Document ID	EO-BEB6F3820B
Generated	2026-07-31

Product Overview

Protective hose

Protection tube, material: PA 6, spiral: without, UV resistant: yes, flexible, protection index: IP68, color: black, flammability class according to UL94: V0, inner diameter: 7 mm, Total length: 50 m

Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 7 mm, Total length: 50 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Technical dataNotesNotes on operation Protective hose length is measured stretched out; length tolerance $\pm 5\%$

General UV-resistant

Product propertiesProduct type Protective hose

Tensile strength GRP 100 N

Data management status

Article revision 00

DimensionsExternal dimensions

Outside diameter 10 mm

Internal dimensions

Internal diameter 6.5 mm

Material specificationsMaterial PA 6

Flammability rating according to UL 94 V0
Components free from silicone, halogen, and cadmium
Cable/line Bending radius, dynamic 35 mm
Bending radius, static 13 mm
Tensile strength 100 N
Halogen-free yes
Environmental and real-life conditions Ambient conditions
Degree of protection IP68
IP69K
Ambient temperature (operation) -40 °C ... 120 °C
Resistance to UV radiation yes
Short-term temperature 150 °C
ETIM for 3240680 Flexible conduit systems (EC001177)
Feature Name
Feature Value
Nominal diameter (EF005114)
10 mm
Outer diameter (EF000015)
10 mm
Inner diameter (EF000065)
6.5 mm
Material (EF002169)
Polyamide (PA)
Sheathing material (EF001745)
Other
Operating temperature (EF001742)
-40 °C
Degree of protection (IP) (EF005474)
IP68
Tensile strength (EF002782)
100 N
Bending radius, static (EF001744)
13 mm
Halogen free (EF000025)
Yes
Plain interior (EF001769)
No
Plain exterior (EF002479)
No
Flexibility (EF001770)
Flexible
Colour (EF000007)
Black
Approved according to DIN EN 61386-23 (EF008144)
No
Approved according to UR (EF001772)
No

Approved according to N (EF001773)

No

Approved according to CSA (EF001784)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-PA HF 10,0 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.