

INDUSTRIAL COMPONENT DATA

PTRV 8-FE /BKYE 3270149 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTRV 8-FE /BKYE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTRV 8-FE /BKYE
Catalog number	3270149
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-81ED4D794A
Generated	2026-08-03

Product Overview

Potential distributors

Potential distributor, nominal voltage: 250 V, nominal current: 17.5 A, connection type: Push-in connection, 1., 2., 3., 4., 5., 6., 7. and 8th floor, Sizing section: 1.5 mm², cross-section: 0.14 mm² - 2.5 mm², mounting: NS 35/7.5, NS 35/15, color: gray, connection elements color: black, yellow

Potential transfer case, rated voltage: 250 V, rated current: 17.5 A, connection type: Push-in connection, 1., 2., 3., 4., 5., 6., 7. and 8. table, dimensioning section: 1.5 mm², cross-section: 0.14 mm² - 2.5 mm², mounting: NS 35/7.5, NS 35/15, colour: grey, connecting elements colour: black, yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3270149

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 49 (C-1-2017)

GTIN 4055626046709

Weight per Piece (excluding packing) 33.750 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 2

Number of levels 8

Number of connections 32

Potentials 1

Nominal cross section 1.5 mm²

Color gray

Color of connection elements black (4x top)

yellow (4x bottom)

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)

Maximum load current 20 A (in case of a 2.5 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)

Nominal current I_N 17.5 A

Nominal voltage U_N 250 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending tes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTRV 8-FE /BKYE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.