

INDUSTRIAL COMPONENT DATA

MACX MCR-PTB 2865625 PHOENIX CONTACT Power and error message module

Brand: PHOENIX CONTACT | Manufacturer Part Number: MACX MCR-PTB



Manufacturer	PHOENIX CONTACT
MPN / Reference	MACX MCR-PTB
Catalog number	2865625
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-53A1A1E19F
Generated	2026-07-31

Product Overview

Power and error message module

Power supply and error signalling module with screw connection, bus connector for corresponding rail ME 17.5 TBUS 1.5/5-ST-3.81 GY included

Power supply and error message module with screw connection, including connector for ME 17.5 TBUS 1.5/5-ST-3.81 GY support rail

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2865625

Packing unit 1 pc

Catalog page Page 174 (C-5-2017)

GTIN 4046356324618

Weight per Piece (excluding packing) 150.800 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Width 17.5 mm

Height 99 mm

Depth 114.5 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -20 °C ... 60 °C (Any mounting position)

Ambient temperature (storage/transport) -40 °C ... 80 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Degree of pollution 2

General

Degree of protection IP20

Standards and Regulations

Designation Electromagnetic RF field

Standards/regulations EN 61000-4-3

Evaluation criterion A

Standards/regulations EN 61000-4-4

Designation Conducted interferences

Standards/regulations EN 61000-4-6

Evaluation criterion A

Flammability rating according to UL 94 V0

Conformance CE-compliant

ATEX ? II 3 G Ex nA nC IIC T4 Gc X

IECEx Ex nA nC IIC T4 Gc X

UL, USA/Canada UL 61010 Listed

Class I, Div. 2, Groups A, B, C, D T5

Class I, Zone 2, Group IIC

DNV GL-Temperature B

DNV GL-Humidity B

DNV GL-Vibration A

DNV GL-EMC B

DNV GL-Enclosure Required protection according to the Rules shall be provided upon installation on board

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127242610eCl@ss 6.027242610eCl@ss 7.027242610...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MACX MCR-PTB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.