

INDUSTRIAL COMPONENT DATA

VS-P1220-P1220-C1020/ 2,0 1609183 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-P1220-P1220-C1020/ 2,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-P1220-P1220-C1020/ 2,0
Catalog number	1609183
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-009F483223
Generated	2026-08-01

Product Overview

Cable

Ready-made PROFINET power cable, 24 V, 5 x 2.5 mm², flexible (50 wires), color RAL 7001 (silver gray), PPC-MSTB metal to PPC-MSTB metal, length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1609183

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 370 (C-2-2017)

GTIN 4046356160100

Weight per Piece (excluding packing) 470.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -40 °C ... 70 °C (cable, fixed installation)

-5 °C ... 70 °C (cable, flexible installation)

Plug / socket

General data

Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 11 Connectors for 24 Volt Power Supply Cabling and Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)

Rated voltage 24 V

Number of positions 5

Alternative short product description PROFINET power cable

Locking type Push Pull

Rated voltage (III/3) 24 V

Contact material Copper alloy

Contact carrier material PA

Contact surface material Gold over nickel

Housing material Zinc die-cast

Cable

Cable type PVC gray

Cable type (abbreviation) PVC

Conductor cross section 5x 2.5 mm²

AWG power supply 14

Conductor structure, voltage supply 50x 0.25 mm

Wire colors blue, brown, black, gray, green/yellow

Overall twist 5 cores, twisted

External sheath, color gray RAL 7001

External cable diameter D 11.8 mm

Minimum bending radius, fixed installation 4 x D

Minimum bending radius, flexible installation 15 x D

Cable weight 242 kg/km

Outer sheath, material PVC

Material cond...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-P1220-P1220-C1020/ 2,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.