

INDUSTRIAL COMPONENT DATA

VS-ST-LK-3,6/22,4/2,6 1688243 PHOENIX CONTACT D-SUB power contact

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-ST-LK-3,6/22,4/2,6



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-ST-LK-3,6/22,4/2,6
Catalog number	1688243
Category	Accessories/spare parts for industrial connectors
Minimum order	100 Pcs
Document ID	EO-1BB0AB3D92
Generated	2026-08-02

Product Overview

D-SUB power contact

Power contacts, for D-SUB combination inserts, male, straight solder cup, 20 A sizing current, gold-plated

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1688243

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

Catalog page Page 447 (C-2-2017)

GTIN 4017918179649

Weight per Piece (excluding packing) 2.050 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Insertion/withdrawal cycles >= 500

Connection method Solder cup

Type of contact Pin

Conductor cross section 2 mm² ... 3.5 mm²

Connection cross section AWG 14 ... 12

Insertion force per signal contact ≤ 7.00 N

Extraction force per signal contact approx. 5 N

Insulation resistance ≥ 5 G?

Contact type turned

Note Power contacts must be ordered separately since they are not included in the scope of supply of the contact carriers.

Ambient conditions

Ambient temperature (operation) -55 °C ... 130 °C

Material data

Contact material Copper alloy

Contact surface material Au/Sn

Electrical characteristics

Rated current 20 A (at 20 °C)

Test voltage 1000 V

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss

7.027440204eCl@ss 8.027440204eCl@ss 9.027440204

ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000796ETIM 5.0EC000796ETIM 6.0EC000796

UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0139121522UNSPSC 13.23...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-ST-LK-3,6/22,4/2,6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.