

INDUSTRIAL COMPONENT DATA

**VS-ST-LK-3,6/22,4/4,6 1688269 PHOENIX CONTACT D-SUB
power contact**

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-ST-LK-3,6/22,4/4,6



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-ST-LK-3,6/22,4/4,6
Catalog number	1688269
Category	Accessories/spare parts for industrial connectors
Minimum order	100 Pcs
Document ID	EO-3BD938E2AD
Generated	2026-08-04

Product Overview

D-SUB power contact

Power contacts, for D-SUB combination inserts, male, straight solder cup, 40 A sizing current, gold

Power contacts, for D-SUB combination inserts, pin, solder cup, straight, rated current 40 A, gold-plated

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesGeneral Power contacts must be ordered separately since they are not included in the scope of supply of the contact carriers.

Product propertiesProduct type Contacts

Type Individual male contact

Contact material type turned

Data management status

Article revision 02

Electrical propertiesMaximum load current 40 A

Rated surge voltage 1 kV

Rated current 40 A (at 20 °C)

Insulation resistance >= 5 G?

Test voltage 1000 V

Connection dataMaximum load current 40 A

Connection method Solder cup
DimensionsWidth 5.5 mm
Height 5.5 mm
Length 22.9 mm
Mechanical characteristics
Contact diameter 4.6 mm
Material specificationsMaterial Metal
Contact material Copper alloy
Contact surface material Au/Sn
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 500
Insertion force per signal contact ≤ 7.00 N
Extraction force per signal contact approx. 5 N
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) $-55^{\circ}\text{C} \dots 130^{\circ}\text{C}$
MountingMounting type Solder connection
ETIM for 1688269 Connectors (EC000796)
Feature Name
Feature Value
Contact type (EF001587)
Pin
Ambient temperature (EF002386)
 130°C
Diameter plug-in contact (EF007320)
4.6 mm
Material contact (EF007544)
Copper
Min. number of insertion cycles (EF012212)
500

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-ST-LK-3,6/22,4/4,6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.