

INDUSTRIAL COMPONENT DATA

VS-PPC-J-4X-1227 1405387 PHOENIX CONTACT Power distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-J-4X-1227



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-J-4X-1227
Catalog number	1405387
Category	Fibre optic attenuator
Minimum order	1 Pcs
Document ID	EO-0CBFA92AF0
Generated	2026-07-29

Product Overview

Power distributor

H Power distributor, 4 MSTB contact inserts, metal housing, without fixing screws

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1405387

Packing unit 1 pc

Catalog page Page 369 (C-2-2017)

GTIN 4046356419918

Weight per Piece (excluding packing) 133.600 g

Custom tariff number 85444290

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -5 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

General data

Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET

regulations, version 2.00, order no: 2.252, Chapter 11 Connectors for 24 Volt Power Supply Cabling and Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)

Rated current at 40°C 16 A

Rated voltage 24 V

Number of positions 5

Degree of pollution 2

Alternative short product description Power H distributor

Locking type Push Pull

Rated voltage (II/2) 630 V

Rated voltage (III/2) 400 V

Rated voltage 250 V

Rated surge voltage (II/2) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (III/3) 4 kV

Rated current 16 A

Rated voltage (III/3) 24 V

Contact carrier material PA

Contact surface material Gold over nickel

Housing material Zinc die-cast

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 10.0.127440390eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.1272607...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-J-4X-1227 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.