

INDUSTRIAL COMPONENT DATA

MINI-BAT/24DC/1.3AH 2866417 PHOENIX CONTACT Energy storage

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI-BAT/24DC/1.3AH



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI-BAT/24DC/1.3AH
Catalog number	2866417
Category	Battery (lithium) for vehicles and applications
Minimum order	1 Pcs
Document ID	EO-6B4B579482
Generated	2026-07-27

Product Overview

Energy storage

Energy accumulator, lead AGM, VRLA technology, 24 V DC, 1.3 Ah.

Battery module, lead AGM, VRLA technology, 24 V DC, 1.2 Ah.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Technical dataNotesGeneral

Note on the battery This product contains a battery with a limited shelf life that must be charged every few months. The product packaging indicates when the battery must be started up or recharged. The general shelf life can be found in the technical data area under "Latest startup".

Input dataInput voltage 24 V DC

Buffer period 20 min. (2 A)

5 min. (5 A)

Output dataNominal output voltage 24 V DC

Output current I_{max} 15 A

Output fuse 1x 15 A

Connection in parallel 5

Connection in series no

Battery operation

Nominal output voltage 24 V DC
Nominal output current (IN) 15 A
Energy storageEnd-of-charge voltage 27.6 V
Charging current 0.36 A
Nominal capacity 1.2 Ah
Battery module service life 6 Years (20 °C)
Latest startup (battery only) - range 6 Months (0 °C ... 20 °C)
6 Months (20 °C ... 30 °C)
3 Months (30 °C ... 40 °C)
Battery technology VRLA-AGM
Memory medium Lead rechargeable battery module
Accumulator type BB Battery BP1.2-12FR
Number of cells 1
Size designation Block
Battery pack yes
IQ technology no
Suitable for fast charging yes
Product propertiesProduct type Battery module
Product family Battery module
Application for MINI DC-UPS
Disposal Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
IQ technology no
Data management status
Article revision 05
Insulation characteristics
Protection class III
DimensionsWidth 52 mm
Height 130 mm
Depth 110 mm
Inst...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI-BAT/24DC/1.3AH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.