

**INDUSTRIAL COMPONENT DATA**

# QUINT-PS/1AC/24DC/20/CO 2320898 PHOENIX CONTACT

## Power supply, with protective coating

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT-PS/1AC/24DC/20/CO



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | QUINT-PS/1AC/24DC/20/CO |
| Catalog number  | 2320898                 |
| Category        | DC-power supply         |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-7822EA0A8E           |
| Generated       | 2026-08-04              |

### Product Overview

Power supply, with protective coating

Primary Switching Power Supplies, QUINT POWER, Screw Connection, Rail Mounting, SFB Technology (Selective Fuse Breaking), Input:1Phase, Output: 24 VDC / 20 A

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                       |
|--------------|---------------------------------------|
| Catalog path | PHOENIX CONTACT > Power Supplies (PS) |
|--------------|---------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 2320898

Packing unit 1 pc

Catalog page Page 217 (C-4-2017)

GTIN 4046356520003

Weight per Piece (excluding packing) 1,700.000 g

Custom tariff number 85044030

Country of origin TH (Thailand)

Dimensions

Width 90 mm

Height 130 mm

Depth 125 mm

Width with alternative assembly 122 mm

Height with alternative assembly 130 mm  
Depth with alternative assembly 93 mm  
Ambient conditions  
Degree of protection IP20  
Ambient temperature (operation) -40 °C ... 70 °C (> 60 °C Derating: 2.5 %/K)  
Ambient temperature (storage/transport) -40 °C ... 85 °C  
Max. permissible relative humidity (operation) 100 % (at 25 °C, non-condensing)  
Climatic class 3K3 (in acc. with EN 60721)  
Degree of pollution 2  
Installation height 6000 m  
Input data  
Nominal input voltage range 100 V AC ... 240 V AC  
110 V DC ... 250 V DC  
Input voltage range 85 V AC ... 264 V AC  
90 V DC ... 410 V DC +5 % (UL 508: ≤ 250 V DC)  
Dielectric strength maximum 300 V AC  
AC frequency range 45 Hz ... 65 Hz  
Frequency range DC 0 Hz  
Discharge current to PE < 3.5 mA  
Current consumption 5.1 A (120 V AC)  
2.3 A (230 V AC)  
4.9 A (110 V DC)  
2.4 A (220 V DC)  
Nominal power consumption 569 VA  
Inrush surge current < 20 A  
Mains buffering typ. 32 ms (120 V AC)  
typ. 32 ms (230 V AC)  
Input fuse 12 A (slow-blow, internal)  
Choice of suitable circuit breakers 10 A ... 16 A (AC: Characteristics B, C, D, K)  
Type of protection Transient surge protection  
Protective circuit/component Varistor, gas-filled surge arrester  
Output data  
Nominal ou...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT-PS/1AC/24DC/20/CO with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.