

INDUSTRIAL COMPONENT DATA

QUINT-PS/1AC/24DC/ 3.5 2866747 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT-PS/1AC/24DC/ 3.5



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT-PS/1AC/24DC/ 3.5
Catalog number	2866747
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-4ACD88A6B4
Generated	2026-08-04

Product Overview

Power supply unit

Primary switching power supplies, QUINT POWER, Screw connection, SFB Technology (Selective Fuse Breaking), input:1phase, output: 24 VDC / 3.5 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2866747

Packing unit 1 pc

Catalog page Page 210 (C-4-2017)

GTIN 4046356113779

Weight per Piece (excluding packing) 500.000 g

Custom tariff number 85044030

Country of origin TH (Thailand)

Dimensions

Width 32 mm

Height 130 mm

Depth 125 mm

Width with alternative assembly 122 mm

Height with alternative assembly 130 mm
Depth with alternative assembly 35 mm
Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -25 °C ... 70 °C (> 60 °C Derating: 2.5 %/K)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)
Climatic class 3K3 (in acc. with EN 60721)
Degree of pollution 2
Installation height 5000 m
Input data
Nominal input voltage range 100 V AC ... 240 V AC
Input voltage range 85 V AC ... 264 V AC
90 V DC ... 350 V DC
Dielectric strength maximum 300 V AC
AC frequency range 45 Hz ... 65 Hz
Frequency range DC 0 Hz
Discharge current to PE < 3.5 mA
Current consumption 1.4 A (120 V AC)
0.8 A (230 V AC)
0.9 A (110 V DC)
0.4 A (220 V DC)
Nominal power consumption 180 VA
Inrush surge current < 20 A (typical)
Mains buffering typ. 20 ms (120 V AC)
typ. 80 ms (230 V AC)
Input fuse 5 A (slow-blow, internal)
Choice of suitable circuit breakers 6 A ... 20 A (AC: Characteristics B, C, D, K)
Type of protection Transient surge protection
Protective circuit/component Varistor
Output data
Nominal output voltage 24 V DC ±1 %
Setting range of the output voltage (USet)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT-PS/1AC/24DC/ 3.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.