

INDUSTRIAL COMPONENT DATA

STEP-PS/ 1AC/24DC/0.75 2868635 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: STEP-PS/ 1AC/24DC/0.75



Manufacturer	PHOENIX CONTACT
MPN / Reference	STEP-PS/ 1AC/24DC/0.75
Catalog number	2868635
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-3C7AE77F9E
Generated	2026-08-03

Product Overview

Power supply unit

STEP POWER primary switch-mode power supply for rail mounting, input: single-phase, output: 24 V DC/0.75 A

Primary clocked power supply STEP POWER for DIN rail mounting, input: 1-phase, output: 24 V DC / 0.75 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Key Commercial Data

Orderkey 2868635

Packing unit 1 pc

Catalog page Page 239 (C-4-2017)

GTIN 4046356165297

Weight per Piece (excluding packing) 110.000 g

Custom tariff number 85044030

Country of origin PL (Poland)

Dimensions

Width 36 mm

Height 90 mm

Depth 61 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 55° C derating : 2.5%/K)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Input data

Nominal input voltage range 100 V AC ... 240 V AC

Input voltage range 85 V AC ... 264 V AC

95 V DC ... 250 V DC

AC frequency range 45 Hz ... 65 Hz

Frequency range DC 0 Hz

Current consumption 0.3 A (120 V AC)

0.2 A (230 V AC)

Nominal power consumption 36.9 VA

Inrush surge current < 15 A (typical)

Mains buffering typ. 15 ms (120 V AC)

typ. 70 ms (230 V AC)

Input fuse 1.25 A (slow-blow, internal)

Choice of suitable circuit breakers 6 A ... 16 A (Characteristics B, C, D, K)

Power factor (cos phi) 0.58

Type of protection Transient surge protection

Protective circuit/component Varistor

Output data

Nominal output voltage 24 V DC ±1 %

Nominal output current (IN) 0.75 A (-25 °C ... 55 °C)

0.83 A (-25°C ... 40°C permanent)

Output current I_{max} 1.4 A

Derating 55 °C ... 70 °C (2.5%/K)

Connection in parallel Yes, for redundancy and increased capacity

Connection in series yes

Feedback resistance ≤ 35 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STEP-PS/ 1AC/24DC/0.75 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.