

INDUSTRIAL COMPONENT DATA

STEP-PS/ 1AC/24DC/3.8/C2LPS 2868677 PHOENIX CONTACT

Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: STEP-PS/ 1AC/24DC/3.8/C2LPS



Manufacturer	PHOENIX CONTACT
MPN / Reference	STEP-PS/ 1AC/24DC/3.8/C2LPS
Catalog number	2868677
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-FC8EC0441A
Generated	2026-08-03

Product Overview

Power supply unit

STEP POWER Primary Switching Power Supply for Rail Mounting, Input: Single Phase, Output: 24 V DC/3.8 A
Primary-switched STEP POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/3.8 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Technical dataInput dataAC operation

Nominal input voltage range 100 V AC ... 240 V AC

Input voltage range 85 V AC ... 264 V AC

95 V DC ... 250 V DC

Input voltage range AC 85 V AC ... 264 V AC

Input voltage range DC 95 V DC ... 250 V DC

Voltage type of supply voltage AC/DC

Inrush current < 15 A (typical)

Inrush current integral (I_{2t}) < 1 A²s

AC frequency range 45 Hz ... 65 Hz

Mains buffering time typ. 25 ms (120 V AC)

typ. 120 ms (230 V AC)

Current consumption 1.3 A (120 V AC)

0.8 A (230 V AC)

Nominal power consumption 175.8 VA

Protective circuit Transient surge protection; Varistor

Power factor (cos phi) 0.59

Typical response time < 0.5 s

Input fuse 4 A (slow-blow, internal)

Recommended breaker for input protection 6 A ... 16 A (Characteristics B, C, D, K)

Output data Efficiency > 88 % (for 230 V AC and nominal values)

Output characteristic U/I

Nominal output voltage 24 V DC

Setting range of the output voltage (USet) 22.5 V DC ... 25 V DC (> 24 V DC, constant capacity restricted)

Output current I_{max} 6.5 A

Nominal output current (I_N) 3.8 A (-25 °C ... 55 °C)

Derating 55 °C ... 70 °C (2.5 %/K)

Feedback voltage resistance ≤ 35 V DC

Protection against overvoltage at the output (OVP) < 35 V DC

Control deviation < 1 % (change in load, static 10 % ... 90 %)

< 2 % (change in load, dynamic 10 % ... 90 %)

< 0.1 % (change in input voltage ±10 %)

Residual ripple < 80 mVPP(20 MHz)

Output power 91.2 W

Peak switching voltages nominal load < 10 mVPP(20 MHz)

Maximum no-load power dissipation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STEP-PS/ 1AC/24DC/3.8/C2LPS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.