

INDUSTRIAL COMPONENT DATA

STEP-PS/ 1AC/24DC/4.2 2868664 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: STEP-PS/ 1AC/24DC/4.2



Manufacturer	PHOENIX CONTACT
MPN / Reference	STEP-PS/ 1AC/24DC/4.2
Catalog number	2868664
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-AC83C2FE23
Generated	2026-07-31

Product Overview

Power supply unit

STEP POWER Primary Switch-On Power Rail Mountable Power Supply, Input: Single Phase, Output: 24 V DC/4.2 A
Primary-switched STEP POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/4.2 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Technical dataInput dataAC operation

Nominal input voltage range 100 V AC ... 240 V AC

Input voltage range 85 V AC ... 264 V AC

95 V DC ... 250 V DC

Input voltage range AC 85 V AC ... 264 V AC

Input voltage range DC 95 V DC ... 250 V DC

Voltage type of supply voltage AC/DC

Inrush current < 15 A (typical)

Inrush current integral (I_{2t}) < 1 A²s

AC frequency range 45 Hz ... 65 Hz

Frequency range DC 0 Hz

Mains buffering time typ. 20 ms (120 V AC)

typ. 100 ms (230 V AC)

Current consumption 1.3 A (120 V AC)
0.8 A (230 V AC)
Nominal power consumption 196.7 VA
Protective circuit Transient surge protection; Varistor
Power factor (cos phi) 0.58
Typical response time < 0.5 s
Input fuse 4 A (slow-blow, internal)
Recommended breaker for input protection 6 A ... 16 A (Characteristics B, C, D, K)
Output data Efficiency > 88 % (for 230 V AC and nominal values)
Output characteristic U/I
Nominal output voltage 24 V DC
Setting range of the output voltage (USet) 22.5 V DC ... 29.5 V DC (> 24 V DC, constant capacity restricted)
Output current I_{max} 6.5 A
Nominal output current (I_N) 4.2 A (-25 °C ... 55 °C)
4.4 A (-25 °C ... 40 °C permanent)
Derating 55 °C ... 70 °C (2.5 %/K)
Feedback voltage resistance ≤ 35 V DC
Protection against overvoltage at the output (OVP) < 35 V DC
Control deviation < 1 % (change in load, static 10 % ... 90 %)
< 2 % (change in load, dynamic 10 % ... 90 %)
< 0.1 % (change in input voltage ±10 %)
Residual ripple < 40 mVPP(20 MHz)
Output power 100.8 W
Peak switching voltages no...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STEP-PS/ 1AC/24DC/4.2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.