

INDUSTRIAL COMPONENT DATA

STIO-IN 2,5/3-PE OG 3209086 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STIO-IN 2,5/3-PE OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	STIO-IN 2,5/3-PE OG
Catalog number	3209086
Category	Sensor/actuator terminal block
Minimum order	25 Pcs
Document ID	EO-837FF8523E
Generated	2026-08-02

Product Overview

Installation ground terminal block

Ground terminal block for distribution, nominal voltage: 250 V, nominal current: 30 A, number of connections: 4, connection type: Spring connection, Sizing cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: orange

Installation Protective Conductor Terminal, Nominal Voltage: 250 V, Rated Current: 30 A, Number of Connections: 4, Connection Type: Tension Spring Connection, Rated Cross-Section: 2.5 mm², Cross-Section: 0.08 mm² - 4 mm², Mounting Type: NS 35/7.5, NS 35/15, Colour: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3209086

Packing unit 25 pc

Catalog page Page 160 (C-1-2017)

GTIN 4046356143288

Weight per Piece (excluding packing) 14.170 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 3
Number of connections 4
Nominal cross section 2.5 mm²
Color orange
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2
Nominal current I_N 30 A (For central infeed and 4 mm² conductor cross section)
18 A (For single-sided infeed and 2.5 mm² conductor cross section)
Maximum load current 30 A (with 4 mm² conductor cross section)
Nominal voltage U_N 250 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 4.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.5 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.08 mm² / 0.1 kg
2.5 mm² / 0.7 kg
4 mm² /....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STIO-IN 2,5/3-PE OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.