

INDUSTRIAL COMPONENT DATA

PP 2,5/ 8 3211287 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP 2,5/ 8



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP 2,5/ 8
Catalog number	3211287
Category	Terminal block connector
Minimum order	25 Pcs
Document ID	EO-E6B30CF40C
Generated	2026-07-29

Product Overview

Plug

Connector, rated voltage: 800 V, rated current: 24 A, number of connections: 8, number of poles: 8, connection type: Push-in connection, 1st floor, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3211287

Packing unit 25 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

Catalog page Page 296 (C-1-2017)

GTIN 4055626285603

Weight per Piece (excluding packing) 25.690 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 8

Number of levels 1

Number of connections 8

Potentials 8

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Area of application Machine building

Plant engineering

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W (the value is based on one connection block and is multiplied according to the pin assignment)

Maximum load current 24 A (with 4 mm² conductor cross section)

Nominal current I_N 24 A

Nominal voltage U_N 800 V

Open side panel No

Dimensions

Width 41.6 mm

Length 16 mm

Height 41.2 mm

25.6 mm

Pitch 5.2 mm

Connection data

Connection method Push-in connection

Stripping length 8 mm ... 10 mm

Connection in acc. with standard IEC 61984

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 12

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 2.5 mm²

Min. AWG conductor cross section, flexible 26

Max. AWG conductor cross section, flexible 14

Conductor cross section flexible, with ferrule w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP 2,5/ 8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.