

INDUSTRIAL COMPONENT DATA

PP-H 1,5/S/1-L/P-GN 1186132 PHOENIX CONTACT Connector, rated voltage: 500 V, rated current: 17.5 A, number o..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP-H 1,5/S/1-L/P-GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP-H 1,5/S/1-L/P-GN
Catalog number	1186132
Category	Terminal block connector
Minimum order	50 Pcs
Document ID	EO-77E1E6C3EB
Generated	2026-08-06

Product Overview

Connector, rated voltage: 500 V, rated current: 17.5 A, number of connections: 1, number of poles: 1, connection type: Push-in connection, Sizing cross-section: 1.5 mm², 1st floor, cross-section: 0.14 mm² - 1.5 mm², color: gray

Connector, rated voltage: 500 V, rated current: 17.5 A, connection type: Push-in connection, number of connections: 1, number of poles: 1, section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, width: 3.5 mm, height: 31.3 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1186132 Terminal blocks (EC002021)

Feature Name

Feature Value

Model (EF000010)

Pin insert

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Total number of poles (without ground contact) (EF006240)

1

Width (EF000008)

3.5 mm

Connectable (EF006169)

Yes

Number of poles (EF001391)

1

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP-H 1,5/S/1-L/P-GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.