

INDUSTRIAL COMPONENT DATA

PP-RJ-RJ 2703015 PHOENIX CONTACT Patch panels

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP-RJ-RJ



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP-RJ-RJ
Catalog number	2703015
Category	Patch panel copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-C24A9BD427
Generated	2026-07-29

Product Overview

Patch panels

Patch panel, two RJ45 female connectors, 10/100/1000 MBit/s, DIN rail adapter, IP20

Patch panel, two RJ45 jacks, CAT6, 10/100/1000 Mbps, DIN rail adapter, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Technical dataNotesNote on application

Note on application Only for industrial use

Utilization restriction

CCCex note Use in potentially explosive areas is not permitted in China.

Product propertiesProduct type Patch panel

MTTF 105699 Years

Data management status

Article revision 06

Insulation characteristics

Overvoltage category II

Pollution degree 2

Electrical propertiesMaximum power dissipation for nominal condition 0 W (passive module, no supply voltage required)

Rated insulation voltage 85 V DC (In accordance with EN/IEC 60079-7, Annex H)

InterfacesData: Ethernet interface, 10/100/1000Base-T(X) in accordance with IEEE 802.3

Serial transmission speed 10/100/1000 Mbps
Frequency range 250 MHz
Connection method RJ45 jack
Note on the connection method CAT6
Pin assignment 1:1
Transmission length 100 m (including patch cables)
Transmission medium Copper
Output nominal voltage < 57 V DC
Maximum output power 60 W
Maximum output current 725 mA (Per channel)
Data: Ethernet interface, 10/100/1000Base-T(X) in accordance with IEEE 802.3
Connection method RJ45 jack
DimensionsDimensional drawing
Width 23.8 mm
Height 101.3 mm
Depth 50 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Material (Housing) Plastic
Flammability rating according to UL 94 V0
Environmental and real-life conditionsAmbient conditions
Degree of protection IP20 (Manufacturer's declaration)
Ambient temperature (operation) -40 °C ... 75 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Altitud...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP-RJ-RJ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.