

INDUSTRIAL COMPONENT DATA

PP-RJ-RJ-F 2703020 PHOENIX CONTACT Patch panels

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP-RJ-RJ-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP-RJ-RJ-F
Catalog number	2703020
Category	Patch panel copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-B39DFBCD35
Generated	2026-07-29

Product Overview

Patch panels

Patch panel, two RJ45 female connectors, 10/100/1000 MBit/s, DIN rail adapter, IP20, shielding current control, surge protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2703020

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626463308

Weight per Piece (excluding packing) 124.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 23.8 mm

Height 101.3 mm

Depth 86 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Altitude 5000 m (For restrictions see manufacturer's declaration)

2000 m (ATEX approval)

Degree of protection IP20 (Manufacturer's declaration)

General

Electrical isolation FE // Ethernet

Standards/regulations DIN EN 61643-21

Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU

Net weight 124.2 g

Housing material Plastic

Color gray

MTTF 3281 Years (SN 29500 standard, temperature 25 °C, operating cycle 21 % (5 days a week, 8 hours a day))

1245 Years (SN 29500 standard, temperature 40 °C, operating cycle 34.25 % (5 days a week, 12 hours a day))

472 Years (SN 29500 standard, temperature 40 °C, operating cycle 100 % (7 days a week, 24 hours a day))

Degree of pollution 2

Overvoltage category II

Conformance CE-compliant

ATEX ? II 3 G Ex nA nC IIC T4 Gc X (Please follow the special installation instructions in the documentation!)

UL, USA UL 60079-0 Ed. 6 / UL 60079-15 Ed. 4

UL, USA/Canada Class I, Zone 2, AEx nA IIC T4, Ex nA IIC Gc X T4

Class I, Div. 2, Groups A, B, C, D

UL, Canada CSA 22.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP-RJ-RJ-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.