

INDUSTRIAL COMPONENT DATA

PP-RJ-SC-F 2703021 PHOENIX CONTACT Patch panels

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP-RJ-SC-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP-RJ-SC-F
Catalog number	2703021
Category	Patch panel copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-C5912BC9CE
Generated	2026-07-29

Product Overview

Patch panels

Patch panel, RJ45 female connector on screw terminals, 10/100/1000 MBit/s, DIN rail adapter, IP20, protective contact with strain relief, shielding current control, surge protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2703021

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626463339

Weight per Piece (excluding packing) 124.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 23.8 mm

Height 101.3 mm

Depth 86 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Altitude 5000 m (For restrictions see manufacturer's declaration)

2000 m (ATEX approval)

Degree of protection IP20 (Manufacturer's declaration)

General

Electrical isolation FE // Ethernet

Standards/regulations DIN EN 61643-21

Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU

Net weight 124.2 g

Housing material Plastic

Color gray

MTTF 3268 Years (SN 29500 standard, temperature 25 °C, operating cycle 21 % (5 days a week, 8 hours a day))

1238 Years (SN 29500 standard, temperature 40 °C, operating cycle 34.25 % (5 days a week, 12 hours a day))

468 Years (SN 29500 standard, temperature 40 °C, operating cycle 100 % (7 days a week, 24 hours a day))

Degree of pollution 2

Overvoltage category II

Conformance CE-compliant

ATEX ? II 3 G Ex nA nC IIC T4 Gc X (Please follow the special installation instructions in the documentation!)

UL, USA UL 60079-0 Ed. 6 / UL 60079-15 Ed. 4

UL, USA/Canada Class I, Zone 2, AEx nA IIC T4, Ex nA IIC Gc X T4

Class I, Div. 2, Groups A, B, C, D

UL, Canada CSA 22.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP-RJ-SC-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.