

INDUSTRIAL COMPONENT DATA

PPC 1,5/S-NS/1-L GNYE 3062139 PHOENIX CONTACT COMBI receptacle

Brand: PHOENIX CONTACT | Manufacturer Part Number: PPC 1,5/S-NS/1-L GNYE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PPC 1,5/S-NS/1-L GNYE
Catalog number	3062139
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-EF343FD515
Generated	2026-08-05

Product Overview

COMBI receptacle

COMBI coupling, nominal voltage: 500 V, nominal current: 17.5 A, number of connections: 1, number of poles: 3, connection type: Push-in connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/15, NS 35/7.5, colour: yellow-green

COMBI coupling, nom. voltage: 500 V, nominal current: 17.5 A, number of connections: 1, number of positions: 3, connection method: Push-in connection, 1 level, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 1.5 mm², mounting type: NS 35/15, NS 35/7,5, color: green-yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Terminal coupling

Area of application Railway industry

Machine building

Plant engineering

Number of positions 3

Pitch 3.5 mm

Number of connections 1

Number of rows 1

Type other

Potentials 3

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 0.56 W

Connection data Nominal cross section 1.5 mm²

1 level

Stripping length 8 mm

Internal cylindrical gage A1 / B1

Connection in acc. with standard IEC 61984

Conductor cross section rigid 0.14 mm² ... 1.5 mm²

Cross section AWG 26 ... 16 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section, flexible [AWG] 26 ... 16 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1 mm²

Nominal current 17.5 A

Maximum load current 17.5 A (with 1.5 mm² conductor cross section)

Nominal voltage 500 V

Nominal cross section 1.5 mm²

1 level Connection cross sections directly pluggable

Conductor cross section rigid 0.25 mm² ... 1.5 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 1.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm² ... 1 mm²

Dimensions Width 3.5 mm

End cover width 2.2 mm

Height 43 mm

Depth 27.1 mm

Depth....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PPC 1,5/S-NS/1-L GNYE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.