


**INDUSTRIAL COMPONENT DATA**

# PPC 1,5/S-NS/14 (1GNYE/13GY) 3213349 PHOENIX CONTACT COMBI receptacle

Brand: PHOENIX CONTACT | Manufacturer Part Number: PPC 1,5/S-NS/14 (1GNYE/13GY)



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | PHOENIX CONTACT                       |
| MPN / Reference | PPC 1,5/S-NS/14 (1GNYE/13GY)          |
| Catalog number  | 3213349                               |
| Category        | Single- and multi-pole terminal strip |
| Minimum order   | 10 Pcs                                |
| Document ID     | EO-73BA2791C1                         |
| Generated       | 2026-08-04                            |

## Product Overview

COMBI receptacle

COMBI coupling, nominal voltage: 500 V, nominal current: 17.5 A, connection type: Push-in connection, 1st floor, Dimensioning cross-section: 1.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting class: NS 35/15, NS 35/7.5, colour: green/yellow-grey

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3213349

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4046356993913

Weight per Piece (excluding packing) 24.300 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 14

Number of levels 1

Number of connections 1  
Potentials 14  
Nominal cross section 1.5 mm<sup>2</sup>  
Color green/yellow-gray  
Insulating material PA  
Flammability rating according to UL 94 V0  
Area of application Railway industry  
Machine building  
Plant engineering  
Maximum load current 17.5 A (with 1.5 mm<sup>2</sup> conductor cross section)  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 0.56 W  
Maximum load current 17.5 A (with 1.5 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 17.5 A  
Nominal voltage U<sub>N</sub> 500 V  
Open side panel Yes  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PPC 1,5/S-NS/14 (1GNYE/13GY) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.