

INDUSTRIAL COMPONENT DATA

PPC 2,5/15 3000669 PHOENIX CONTACT COMBI receptacle

Brand: PHOENIX CONTACT | Manufacturer Part Number: PPC 2,5/15



Manufacturer	PHOENIX CONTACT
MPN / Reference	PPC 2,5/15
Catalog number	3000669
Category	Terminal block connector
Minimum order	10 Pcs
Document ID	EO-AAEE8E9637
Generated	2026-08-05

Product Overview

COMBI receptacle

COMBI coupling, rated voltage: 500 V, rated current: 24 A, number of connections: 15, number of poles: 15, connection type: Push-in connection, 1st floor, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3000669

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 291 (C-1-2017)

GTIN 4046356676847

Weight per Piece (excluding packing) 53.210 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 15

Number of levels 1

Number of connections 15

Potentials 1

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum load current 24 A (with a 2.5 mm² conductor cross section)

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W

Ambient temperature (operation) -60 °C ... 100 °C

Maximum load current 24 A (with a 2.5 mm² conductor cross section)

Nominal current I_N 24 A

Nominal voltage U_N 500 V

Open side panel Yes

Insertion/withdrawal cycles mechanical 100

Result of surge voltage test Test passed

Surge voltage test setpoint 7.3 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.89 kV

Short circuit stability result Test passed

Conductor cross section short circuit testing 2.5 mm²

Short-time current 0.3 kA

Result of thermal test Test passed

Proof of thermal characteristics (needle flame) effective duration 30 s

Oscillation, broadband noise test result Test passed

Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03

Test spectrum Servi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PPC 2,5/15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.