

INDUSTRIAL COMPONENT DATA

PRC 5-FC-FS6 8-12 1410629 PHOENIX CONTACT Coupler connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PRC 5-FC-FS6 8-12



Manufacturer	PHOENIX CONTACT
MPN / Reference	PRC 5-FC-FS6 8-12
Catalog number	1410629
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-58C640D6B4
Generated	2026-08-05

Product Overview

Coupler connector

Circular connector (cable side), Article family: PRC, Plug-in coupling connector, construction: Unlock only with tool, housing material: PPE, color: black, number of poles: 5, min. conductor cross-section: 1.5 mm², max. conductor cross-section: 6 mm², rated voltage: 690 V AC, assigned current: 35 A, Connection type: Screw connection, Contact type: Female, min. cable diameter: 8.00 mm, max. cable diameter: 12.00 mm. Variant for unlocking with a tool

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1410629

Packing unit 1 pc

Minimum order quantity 10 pc

Catalog page Page 76 (NTK-2014)

GTIN 4046356904223

Weight per Piece (excluding packing) 92.100 g

Custom tariff number 85366990

Country of origin PL (Poland)

General data

Number of positions 5

Protection class II
Color black
Locking type Snap-in locking
Insertion/withdrawal cycles 100
Pull-out-force 175 N $\pm$ 50 N
Insertion force 40 N $\pm$ 10 N
Degree of protection (when plugged in) IP66 / IP68 (2m / 24h) / IP69K
Connection data
Rated current 35 A (With 6 mm² conductor cross section in accordance with IEC 61984)
32 A (With 6 mm² conductor cross section in accordance with IEC 61535)
21.4 A (With 6 mm² conductor cross section and 85 °C in accordance with 2 PfG 1915)
30 A (With 6 mm²/AWG 10, in accordance with UL 2238)
Nominal voltage ATD 690 V AC (in accordance with IEC 61984)
500 V AC (in accordance with IEC 61535/2 PfG 1915)
600 V AC (In accordance with UL 2238)
Rated voltage (III/2) 690 V
Conductor cross section flexible min. 4 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section solid min. 1.5 mm²
Conductor cross section solid max. 6 mm²
Stripping length 12 mm
Torque max. 1 Nm (Contact screw)
Type of contact Socket
Stripping length of the sheath 50 mm
Material data
Contact material Cu alloy
Contact surface material silver-plated
Contact carrier material PPE
Flammability rating according to UL 94 V0
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PRC 5-FC-FS6 8-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.