

INDUSTRIAL COMPONENT DATA

RIF-0-RPT-24DC/21AU 2903368 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-0-RPT-24DC/21AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-0-RPT-24DC/21AU
Catalog number	2903368
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-EBC03003E3
Generated	2026-08-05

Product Overview

Relay Module

Pre-assembled relay module with push-in connection, consisting of: relay socket with ejector and multi-layer gold contact relay. Contact type: 1 inverter contact. Input voltage: 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2903368

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 332 (C-5-2017)

GTIN 4046356732963

Weight per Piece (excluding packing) 28.100 g

Custom tariff number 85364110

Country of origin CN (China)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 93 mm
Depth 78 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN see diagram
Typical input current at UN 9 mA
Typical response time 5 ms
Typical release time 8 ms
Coil voltage 24 V DC
Protective circuit Damping diode
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.22 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgSnO, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Minimum switching voltage 100 mV (at 10 mA)
Min. switching current 1 mA
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
Switching capacity 1 A (24 V (DC13))
3 A (230 V (AC 15))
Contact side (with destroyed gold layer)
Contact material AgSnO
Note the following values are applicable if a gold layer is destroyed
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 5 V (at 100 mA)
Limiting continuous current 6 A
Min. switching...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-0-RPT-24DC/21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.