

INDUSTRIAL COMPONENT DATA

RIF-0-RPT-24DC/ 1 2903361 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-0-RPT-24DC/ 1



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-0-RPT-24DC/ 1
Catalog number	2903361
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-DECFB2A798
Generated	2026-08-03

Product Overview

Relay Module

Pre-assembled relay module with push-in connection, consisting of: relay socket with ejector and relay with power contact.
Contact type: 1 normally open contact. Input voltage: 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2903361

Packing unit 10 pc

Catalog page Page 333 (C-5-2017)

GTIN 4046356731997

Weight per Piece (excluding packing) 24.950 g

Custom tariff number 85364110

Country of origin CN (China)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 93 mm

Depth 66 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN see diagram

Typical input current at UN 9 mA

Typical response time 5 ms

Typical release time 8 ms

Coil voltage 24 V DC

Protective circuit Damping diode

Operating voltage display Yellow LED

Power dissipation for nominal condition 0.22 W

Contact side

Contact type 1 N/O contact

Type of switch contact Single contact

Contact material AgSnO

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 5 V (at 100 mA)

Min. switching current 10 mA (at 12 V)

Maximum inrush current 10 A (4 s)

Limiting continuous current 6 A

Interrupting rating (ohmic load) max. 140 W (at 24 V DC)

20 W (at 48 V DC)

18 W (at 60 V DC)

23 W (at 110 V DC)

40 W (at 220 V DC)

1500 VA (for 250 V AC)

Switching capacity 1 A (24 V (DC13))

0.2 A (at 110 V, DC13)

0.1 A (at 220 V, DC13)

3 A (at 24 V, AC15)

3 A (at 120 V, AC15)

3 A (at 230 V, AC15)

Connection data 1

Connection name Input side

Connection method Push-in connection

Stripping length 8 mm

Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-0-RPT-24DC/ 1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.