

INDUSTRIAL COMPONENT DATA

RIF-2-RPT-LV-24AC/2X21 2903313 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-2-RPT-LV-24AC/2X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-2-RPT-LV-24AC/2X21
Catalog number	2903313
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-5872253A8C
Generated	2026-08-02

Product Overview

Relay Module

Pre-assembled relay module with push-in connection, consisting of: relay socket, relay with power contact, plug-in indication/antiparasitic module and clamping flange. Contact type: 2 investor contacts. Input voltage: 24 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2903313

Packing unit 10 pc

Catalog page Page 350 (C-5-2017)

GTIN 4046356732505

Weight per Piece (excluding packing) 109.100 g

Custom tariff number 85364110

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 31 mm

Height 96 mm

Depth 75 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 50 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 24 V AC

Input voltage range in reference to UN see diagram

Mains frequency 50/60 Hz

Typical input current at UN 66 mA

Typical response time 5 ms ... 15 ms

Typical release time range 5 ms ... 20 ms

Coil voltage 24 V AC

Protective circuit Varistor

Operating voltage display Yellow LED

Power dissipation for nominal condition 1.58 W

Contact side

Contact type 2 PDT

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 5 V (At 24 mA)

Min. switching current 5 mA (at 24 V)

Maximum inrush current 30 A (20 ms, N/O contact)

Limiting continuous current 8.5 A (see diagram)

Interrupting rating (ohmic load) max. 204 W (at 24 V DC)

124 W (at 48 V DC)

108 W (at 60 V DC)

52 W (at 110 V DC)

48 W (at 220 V DC)

2125 VA (for 250 V AC)

Switching capacity 2 A (at 24 V, DC13)

0.22 A (at 120 V, DC13)

0.11 A (at 250 V, DC13)

3 A (at 120 V, AC15)

1.5 A (at 240 V, AC15)

Connection data 1

Connection name Coil side

Conne...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-2-RPT-LV-24AC/2X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.