

INDUSTRIAL COMPONENT DATA

TRIO-PS-2G/3AC/24DC/10 2903154 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: TRIO-PS-2G/3AC/24DC/10



Manufacturer	PHOENIX CONTACT
MPN / Reference	TRIO-PS-2G/3AC/24DC/10
Catalog number	2903154
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-EF24A1F4E1
Generated	2026-08-05

Product Overview

Power supply unit

TRIO POWER primary switching power supply with push-in connection for rail mounting, input: three-phase, output: 24 V DC/10 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2903154

Packing unit 1 pc

Catalog page Page 223 (C-4-2017)

GTIN 4046356960953

Weight per Piece (excluding packing) 1,175.500 g

Custom tariff number 85044030

Country of origin CN (China)

Dimensions

Width 42 mm

Height 130 mm

Depth 160 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 60 °C Derating: 2.5 %/K)

Ambient temperature (start-up type tested) -40 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Installation height ≤ 5000 m (> 2000 m, Derating: 10 %/1000 m)

Input data

Nominal input voltage range 3x 400 V AC ... 500 V AC

2x 400 V AC ... 500 V AC

Input voltage range 3x 400 V AC ... 500 V AC -20 % ... +15 %

2x 400 V AC ... 500 V AC -10 % ... +15 %

AC frequency range 50 Hz ... 60 Hz

Discharge current to PE < 3.5 mA

Current consumption 3x 0.6 A (400 V AC)

3x 0.6 A (500 V AC)

2x 1.1 A (400 V AC)

2x 1.1 A (500 V AC)

Nominal power consumption 451.7 VA

Inrush surge current ≤ 26 A (typical)

Mains buffering typ. 10 ms (400 V AC)

typ. 20 ms (500 V AC)

Input fuse 3.15 A (internal (device protection), slow-blow)

Choice of suitable circuit breakers 6 A ... 16 A (Characteristics B, C, D, K)

Power factor (cos phi) 0.58

Type of protection Transient surge protection

Protective circuit/component Varistor

Output data

Nominal output voltage 24 V DC ±1 %

Settin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TRIO-PS-2G/3AC/24DC/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.