

INDUSTRIAL COMPONENT DATA

PSM-CABLE-PROFIB/FC 2744652 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSM-CABLE-PROFIB/FC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSM-CABLE-PROFIB/FC
Catalog number	2744652
Category	Data and communication cable
Minimum order	1 m.
Document ID	EO-8F81DBA0A7
Generated	2026-07-28

Product Overview

Bus system cable

By meters, Bus system cable, PROFIBUS (12 MBit/s), shielded, PVC FR VI/PVC, violet, 2-conductors (1X2XAWG22/1), color single conductors: red, green, cable length: Free input (1.0 ... 1000.0 m)

By the meter, Bus system cable, PROFIBUS (12 Mbps), shielded, PVC FR VI/PVC, violet, 2-wire (1x2xAWG22/1), color single wire: red, green, cable length: Free entry (1.0 ... 1000.0 m)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable by the meter

Sensor type PROFIBUS

Number of positions 2

Shielded yes

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

Transmission medium Copper

InterfacesSignal type/category PROFIBUS, 12 Mbps

Cable/lineCable length Free entry (1.0 ... 1000.0 m)

Cable weight 80 kg/km

UL AWM Style 21694 (60 °C / 600 V)

Wiring standards/regulations Conductor material DIN EN 13602 Cu-ETP-A...

Shielding material DIN EN 13602 Cu-ETP-A...-B

Number of positions 2

Shielded yes

Conductor structure 1x2xAWG22/1

Signal speed 0.81 c

Conductor structure signal line 1x 0.65 mm

AWG signal line 22

Conductor cross section 2x 0.34 mm²

Wire diameter incl. insulation 2.55 mm

External cable diameter 8.00 mm ±0.4 mm

Outer sheath, material PVC FR VI

External sheath, color violet

Conductor material Bare Cu wire

Material wire insulation PE

Single wire, color red, green

Thickness, insulation 0.95 mm

Thickness, outer sheath 0.90 mm

Overall twist 2 wires, twisted

Optical shield covering 55 %

Insulation resistance $\geq 16 \text{ G}\cdot\text{km}$

Loop resistance $\leq 110.00 \text{ }\Omega/\text{km}$

Cable capacity approx. 28.5 nF/km (at 1 kHz)

$\leq 1500 \text{ pF/km}$ (asymmetrical: Conductor to ground)

Cable impedance 150 $\Omega \pm 10 \%$ (3 ... 20 MHz)

185 $\Omega \pm 10 \%$ (31.25 ... 38.4 kHz)

270 $\Omega \pm 10 \%$ (9.6 kHz)

Test voltage 3600 V DC (3 s)

Smallest bending radius, fixed installation $\geq 150 \text{ mm}$

Tensile strength $\leq 100 \text{ N}$

Shield attenuation $\leq 42.00 \text{ dB/km}$ (at 16 MHz)

$\leq 22.00 \text{ dB}$ (at 4 ΩHz)

$\leq 4.00 \text{ dB}$ (at 38.4 kHz)

$\leq 2.50 \text{ dB}$ (at 9.6 kHz...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSM-CABLE-PROFIB/FC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.