

INDUSTRIAL COMPONENT DATA

VS-OE-PPC/ME-93C-LI/5,0 1416216 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-OE-PPC/ME-93C-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-OE-PPC/ME-93C-LI/5,0
Catalog number	1416216
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-F03715543D
Generated	2026-07-31

Product Overview

Network cable

Ready-made PROFINET cable, CAT5e, shielded, star quadrage, AWG 22 suitable for energy chains (7 wires), RAL 6018 (yellow-green), RJ45/IP67 male connector, push-pull, metal housing, free cable end, Line, length 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1416216

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 308 (PC-2011)

GTIN 4046356474764

Weight per Piece (excluding packing) 332.100 g

Custom tariff number 85444210

Country of origin PL (Poland)

Ambient conditions

Degree of protection IP65

IP67

General data

Number of positions 4
Standards/regulations IEC PAS 61076-3-117
Overvoltage category I
Degree of pollution 2
Alternative short product description PROFINET cable
Locking type Push Pull
Characteristics head 2
Material (component) Metal
Standards and Regulations
Standards/regulations IEC PAS 61076-3-117
Flammability rating according to UL 94 V0
Cable
Product labeling "sequential length in metres" PN-CABLE-934-C / PUR-4X22AWG/7 Trailing * 22AWG (SHIELDED) (UL) E119100 CMX 75°C VERIFIED (UL) CAT 5E PATCH CABLE FRNC * (Cable printing cable supplier)
Cable type PROFINET drag chain CAT5
Cable type (abbreviation) 93C
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
EtherCAT®CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.5 mm
Wire colors White, yellow, blue, orange
Overall twist Star quad
Shielding Aluminum-coated foil, tinned copper braided shield
Optical shield covering 85 %
External sheath, color green RAL 6018
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bending radius, fixed i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-OE-PPC/ME-93C-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.