

INDUSTRIAL COMPONENT DATA

VS-OE-PPC/PL-93C-LI/5,0 1416222 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-OE-PPC/PL-93C-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-OE-PPC/PL-93C-LI/5,0
Catalog number	1416222
Category	Patch cord copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-7289D4DEA5
Generated	2026-08-02

Product Overview

Network cable

Ready-made PROFINET cable, CAT5e, shielded, star quadage, AWG 22 suitable for energy chains (7 wires), RAL 6018 (yellow-green), RJ45/IP67 male connector, push-pull, plastic housing, free cable end, Line, length 5 m

Assembled PROFINET cable, CAT5e, shielded, star quad, AWG 22 flexible cable conduit capable (7-wire), RAL 6018 (yellow-green), RJ45 plug/IP67 push-pull plastic housing on free conductor end, line, length 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Sensor type PROFINET

Number of positions 4

Connection profile RJ45 8(4)

No. of cable outlets 1

Shielded yes

Cable outlet straight

Data management status

Article revision 10

Insulation characteristics

Overvoltage category I

Degree of pollution 2
Electrical propertiesTransmission medium Copper
Transmission characteristics (category) CAT5 (IEC 11801:2002)
Transmission speed 100 Mbps
Wave impedance 100 ?
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 250
Max. bending cycles 3000000
Material specificationsFlammability rating according to UL 94 V0
Outer sheath, material PUR
Conductor material Tin-plated Cu litz wires
ConnectorConnection 1
Type free cable end
Connection 2
Type Plug straight RJ45
Locking type Push Pull
Handle color black
Material Plastic
Degree of protection IP67
Cable/lineCable length 5.00 m
PROFINET drag chain CAT5 [93C]
Dimensional drawing
Cable weight 61 kg/km
Number of positions 4
Shielded yes
Cable type PROFINET drag chain CAT5 [93C]
Conductor structure 1x4xAWG22/7, SF/TQ
Signal runtime 5.3 ns/m
Signal speed 0.66 c
Conductor structure signal line 7x 0.25 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm²
Wire diameter incl. insulation 1.5 mm
External cable diameter 6.50 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color green RAL 6018
Conductor material Tin-plated Cu litz wires
Material wire insulation PE
Single wire, color white, yellow, blue, orange
Thic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-OE-PPC/PL-93C-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.