

INDUSTRIAL COMPONENT DATA

NBC-M12MSD/ 5,0-93C/R4RC 1416204 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/ 5,0-93C/R4RC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/ 5,0-93C/R4RC
Catalog number	1416204
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-071C3279FD
Generated	2026-08-03

Product Overview

Network cable

Network cable, PROFINET CAT5 (100 MBit/s), EtherCAT® CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 straight connector, encoding: D / IP67, a RJ45 Push-pull straight connector, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1416204

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 308 (PC-2011)

GTIN 4046356474726

Weight per Piece (excluding packing) 402.900 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

General data

Rated voltage 48 V AC

60 V DC

Number of positions 4

Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps

Overvoltage category I

Degree of pollution 3

Alternative short product description PROFINET cable

Characteristics head 1

Head type Plug straight M12

Color black

Characteristics head 2

Head type Plug straight RJ45 Push Pull

Color silver

Standards and Regulations

Flammability rating according to UL 94 V0

Cable

Product labeling "sequential length in metres" PN-CABLE-934-C / PUR-4X22AWG/7 Trailing * 22AWG (SHIELDED) (UL) E119100 CMX 75°C VERIFIED (UL) CAT 5E PATCH CABLE FRNC * (Cable printing cable supplier)

Cable type PROFINET drag chain CAT5

Cable type (abbreviation) 93C

Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps

EtherCAT@CAT5 (IEC 11801), 100 Mbps

Cable structure 1x4xAWG22/7; SF/TQ

Conductor cross section 4x 0.34 mm²

AWG signal line 22

Conductor structure signal line 7x 0.25 mm

Core diameter including insulation 1.5 mm

Wire colors White, yellow, blue, orange

Overall twist Star quad

Shielding Aluminum-coated foil, tinned copper braided shield

Optical shield covering 85 %

External sheath, color green RAL 6018

Outer sheat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/ 5,0-93C/R4RC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.