

INDUSTRIAL COMPONENT DATA

MACX MCR-EX-T-UI-UP-SP 2924689 PHOENIX CONTACT

Temperature measuring transducer

Brand: PHOENIX CONTACT | Manufacturer Part Number: MACX MCR-EX-T-UI-UP-SP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MACX MCR-EX-T-UI-UP-SP
Catalog number	2924689
Category	Temperature transformer
Minimum order	1 Pcs
Document ID	EO-B2E21D61DF
Generated	2026-08-02

Product Overview

Temperature measuring transducer

Programmable intrinsically safe temperature converter with analog output and 1 limit value relay, standard configuration, heat resistance in 2, 3 or 4 conductor technology, thermocouples, galvanic separation, wide power range, push-in connection, SIL, PL.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2924689

Packing unit 1 pc

Catalog page Page 148 (C-5-2017)

GTIN 4046356629102

Weight per Piece (excluding packing) 163.700 g

Custom tariff number 85437090

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Width 17.5 mm

Height 99 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 65 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Maximum altitude ≤ 2000 m

Permissible humidity (operation) typ. 5 % ... 95 % (non-condensing)

Noise immunity EN 61000-6-2 When being exposed to interference, there may be minimal deviations.

Shock 15g, according to IEC 60068-2-27

Vibration (operation) 5g, accordance to IEC 60068-2-6

Input data

Sensor types (RTD) that can be used Pt, Ni, Cu sensors: 2, 3, 4-wire

Sensor types that can be used (TC) B, E, J, K, N, R, S, T, L, U, CA, DA, A1G, A2G, A3G, MG, LG

Temperature measuring range -250 °C ... 2500 °C (Range depending on the sensor type)

Input signal range 0 ? ... 50 k?

Potentiometer resistance range 0 ? ... 50 k?

Input signal range -1000 mV ... 1000 mV

Output data

Configurable/programmable Yes

Max. voltage output signal ± 11 V

Current output signal 4 mA ... 20 mA (in the case of SIL; further free configuration without SIL)

Max. current output signal 22 mA

Load/output load voltage output ≥ 10 k?

Load/output load current output ≤ 600 ? (at 20 mA)

Behavior in the event of a sensor error according to NE 43 or freely configurable

Output name Switching output

Conf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MACX MCR-EX-T-UI-UP-SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.