

INDUSTRIAL COMPONENT DATA

US-PML-P100 (D100) 1014218 PHOENIX CONTACT Prohibition sign

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-PML-P100 (D100)



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-PML-P100 (D100)
Catalog number	1014218
Category	Warning/signing plate
Minimum order	10 Pcs
Document ID	EO-7065BDC409
Generated	2026-08-05

Product Overview

Prohibition sign

Prohibition sign, Card, red/white, pre-printed, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: glued, diameter: 100 mm, usable surface: d: 100 mm, Number of individual indexes: 1

Prohibition sign, Card, red/white, pre-printed, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD: Diagonal bar, mounting type: adhesive, diameter: 100 mm, Number of individual labels: 1, text field height: 100 mm, text field width: 100 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Prohibition sign unprinted

Area of application Prohibition signs

Prohibition marking according to ISO 7010

Type circular

Data management status

Article revision 02

Marking

Number of individual labels 1

Number of individual labels per row 1

Printing Diagonal bar
Identification technology Thermal transfer
Dimensions Width 100 mm
Text field width 100.00 mm
Height 100 mm
Text field height 100.00 mm
Depth 0.09 mm
Diameter 100.00 mm
Min. material thickness 0.09 mm
Material specifications Color multicolored
red (RAL 3001)
white (RAL 9010)
Material PVC
Components Silicone-free
Environmental and real-life conditions Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Ambient temperature (assembly) > 10 °C
Recommended ambient temperature (storage/transport) 22 °C
Recommended humidity (storage/transport) 50 % ... 55 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life 2 years
Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Mounting Mounting type adhesive
ETIM for 1014218 Auxiliary material (EC001777)
Feature Name
Feature Value
Width (EF000008)
100 mm
Height (EF000040)
100 mm
Diameter (EF000551)
100 mm
Colour (EF000007)
Red/white

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-PML-P100 (D100) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.