

INDUSTRIAL COMPONENT DATA

OTTA 6-PE 0790527 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: OTTA 6-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	OTTA 6-PE
Catalog number	0790527
Category	Ground terminal block
Minimum order	1 Pcs
Document ID	EO-FF590521C0
Generated	2026-08-03

Product Overview

Ground modular terminal block

Universal protective conductor terminal with asparagus connection, section: 0.1 ... 6 mm², width: 12 mm, color: green-yellow
Terminals for earth conductors, rated voltage: 800 V, rated current: 41 A, number of connections: 2, connection type: bolt, sizing cross-section: 6 mm², mounting type: M3, mounting type: NS 35/7.5, NS 35/15, NS 32, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 0790527

Packing unit 50 pc

Catalog page Page 535 (C-1-2017)

GTIN 4017918005634

Weight per Piece (excluding packing) 34.390 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 2

Nominal cross section 6 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-2
Nominal current IN 41 A
Maximum load current 41 A (with 6 mm² conductor cross section)
Nominal voltage UN 800 V (the nominal voltage applies to insulated cable lugs)
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail veh...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / OTTA 6-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.