

INDUSTRIAL COMPONENT DATA

PT 2X1-VF-120AC-ST 2856799 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2X1-VF-120AC-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2X1-VF-120AC-ST
Catalog number	2856799
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-7F5AE38862
Generated	2026-07-29

Product Overview

Surge protection plug

Plug-in protection with leakage current-proof protection circuit for two signals without earth potential. Series circuit consisting of varistor and a gas-filled surge arrester between the signal and ground conductors.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2856799

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 114 (C-4-2017)

GTIN 4017918974558

Weight per Piece (excluding packing) 25.600 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 44.8 mm

Width 17.5 mm

Depth 51.7 mm

Horizontal pitch 1 Div.

Complete module height 90 mm

Complete module width 17.7 mm

Complete module depth 65.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Degree of protection IP20

General

Housing material PA 6.6

Flammability rating according to UL 94 V-0

Color black

Standards for clearances and creepage distances IEC 60664-1

DIN VDE 0110-1

Overvoltage category III

Degree of pollution 2

Mounting type on base element

Type Male

Number of positions 2

Direction of action Line-Line & Line-Earth Ground

Arrester can be tested with CHECKMASTER from software version: SW Version 2.13 or later

Protective circuit

IEC test classification C1

C2

C3

Nominal voltage UN 120 V AC

Maximum continuous voltage UC 175 V AC

Rated current 6 A (with PT BE/FM)

Operating effective current $I_{Cat UC} \leq 2 \mu A$

Residual current $I_{PE} \leq 4 \mu A$

Nominal discharge current $I_n(8/20) \mu s$ 3 kA

Pulse discharge current $I_{imp}(10/350) \mu s$ 300 A

Total discharge current $I_{total}(10/350) \mu s$ 8 kA

Max. discharge current $I_{max}(8/20) \mu s$ 8 kA

Nominal pulse current $I_{an}(10/1000) \mu s$ (line-earth) 40 A

Output voltage limitation at 1 kV/ μs (line-earth) static $\leq 800 V$

Residual voltage at I_n (line-earth) $\leq 600 V$

Residual vol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2X1-VF-120AC-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.