

**INDUSTRIAL COMPONENT DATA**

# HC-B 16-SD-MLT/FS-AL 1584525 PHOENIX CONTACT

## Protective covers

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-SD-MLT/FS-AL



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | HC-B 16-SD-MLT/FS-AL          |
| Catalog number  | 1584525                       |
| Category        | Cap for industrial connectors |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-49396C2E51                 |
| Generated       | 2026-08-01                    |

### Product Overview

Protective covers

B16 protective cap, with longitudinal flange, protective cap material: Al, height: 20 mm, seal: yes, retaining cord ring diameter: 30 mm, with lashing cord

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                            |
|--------------|------------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |
|--------------|------------------------------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 1584525

Packing unit 10 pc

Catalog page Page 654 (C-2-2017)

GTIN 4046356145190

Weight per Piece (excluding packing) 112.700 g

Custom tariff number 85389099

Country of origin DE (Germany)

Dimensions

Length 94 mm

Width 43 mm

Height 20 mm

Diameter of retaining cord eyelet 30 mm

Ambient conditions

Degree of protection (IP) IP66

Ambient temperature (operation) -40 °C ... 125 °C

General

Size B16

Type for sleeve housing without single locking latch

Material Aluminum, die-cast

Seal material NBR

Locking latch material High-grade steel, handle: PA-GF

Color gray

Seal present yes

Connection The guide pins of the protective cover must be removed when using coding sockets, pins, and bolts.

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141210eCl@ss 4.127141210eCl@ss 5.027149110eCl@ss 5.127149100eCl@ss 6.027261200eCl@ss  
7.027440208eCl@ss 8.027440208eCl@ss 9.027440208

ETIM 2.0EC000241ETIM 3.0EC002040ETIM 4.0EC002314ETIM 5.0EC002314ETIM 6.0EC002314

UNSPSC 6.0130212113UNSPSC 7.090139121712UNSPSC 1139121712UNSPSC 12.0139121712UNSPSC  
13.239121421

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-SD-MLT/FS-AL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.