

INDUSTRIAL COMPONENT DATA

WP-STEEL ZC 10 3240697 PHOENIX CONTACT Protective hose

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-STEEL ZC 10



Manufacturer	PHOENIX CONTACT
MPN / Reference	WP-STEEL ZC 10
Catalog number	3240697
Category	Protective metallic hose
Minimum order	10 Pcs
Document ID	EO-5F154D6EC9
Generated	2026-08-03

Product Overview

Protective hose

Protection tube, material: Steel, galvanized, protection index: IP40, color: silver, inner diameter: 8 mm, Total length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 3240697

Packing unit 10 M

Minimum order quantity 10 M

Note Made to Order (non-returnable)

Catalog page Page 640 (C-3-2017)

GTIN 4046356736961

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 83071000

Country of origin DE (Germany)

Dimensions

Inner diameter (f) 8 mm

Outside diameter 10 mm

Ambient conditions

Ambient temperature (operation) -200 °C ... 220 °C

Degree of protection IP40

General

Color silver

Type Spirals

Components halogen-free

Material Steel, galvanized

Bending radius, static 20 mm

Bending radius, dynamic 50 mm

Tensile strength 500 N

Standards and Regulations

Halogen-free yes

Classifications

eCl@ss 4.027141131eCl@ss 4.127141131eCl@ss 5.027141131eCl@ss 5.127140900eCl@ss 6.027140900eCl@ss

7.027430301eCl@ss 8.027430301eCl@ss 9.027430301

ETIM 3.0EC000897ETIM 4.0EC001179ETIM 5.0EC001179ETIM 6.0EC001179

UNSPSC 6.0130211812UNSPSC 7.090139121410UNSPSC 1139121411UNSPSC 12.0139121411UNSPSC

13.240141734

ETIM for 3240697 Flexible conduit systems (EC001179)

Feature Name

Feature Value

Nominal diameter (EF005114)

8 mm

Outer diameter (EF000015)

10 mm

Inner diameter (EF000065)

8 mm

Surface protection (EF000139)

Galvanised

Sheathing material 1st coating (EF003660)

Other

Sheathing material 2nd coating (exterior) (EF003661)

Other

Operating temperature (EF001742)

-50 °C

Degree of protection (IP) (EF005474)

IP40

Tensile strength (EF002782)

500 N

Bending radius, static (EF001744)

20 mm

Colour (EF000007)

Other

Flame accelerating (EF001746)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-STEEL ZC 10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.