

INDUSTRIAL COMPONENT DATA

PSR-CT-M-SEN-1-8 2702975 PHOENIX CONTACT Safety switch sensor

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-CT-M-SEN-1-8



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-CT-M-SEN-1-8
Catalog number	2702975
Category	Accessories/spare parts for sensor technology
Minimum order	1 Pcs
Document ID	EO-4ED279B1DB
Generated	2026-07-29

Product Overview

Safety switch sensor

Non-contact safety switch up to cat. 4, PL e (EN ISO 13849), SIL 3 (IEC 61508), RFID-coded multicode sensor, construction type 4 (EN ISO 14119), manual or automatic start, integrated diagnostics, 24 V DC supply, IP69K, M12 connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2702975

Packing unit 1 pc

GTIN 4055626447025

Weight per Piece (excluding packing) 41.100 g

Custom tariff number 85365019

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 26.5 mm

Height 40 mm

Depth 18 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

Power supplySupply voltage 24 V DC $\pm 15\%$ (PELV, controlled, residual ripple)

Current consumption max. 40 mA

Protection min. 0.25 A (to be performed externally)

max. 8 A (to be performed externally)

Alarm outputs

Designation DGN

Output description p-wired

Number of outputs 1

Short-circuit-proof yes

Output voltage min. (UB- 1.5 V (HIGH))

max. (UB(HIGH))

min. 0 V DC (LOW)

max. 1 V DC (LOW)

Current IDGN min. 1 mA

Safety outputs

Designation FO1A, FO1B

Output description Semiconductor outputs, p-wired

Number of outputs 2

Output voltage min. (UB- 1.5 V (HIGH FO1A, FO1B))

max. (UB(HIGH FO1A, FO1B))

min. 0 V DC (LOW FO1A/FO1B)

max. 1 V DC (LOW FO1A/FO1B)

Switching current min. 1 mA (per safety output)

max. 150 mA (per safety output)

Short-circuit-proof yes

Utilization category in accordance with IEC 60947-5-2 150 mA (24 V (DC13))

Note on protection circuit NOTE: Protect the outputs under inductive loads with a freewheeling diode.

Residual current ≤ 0.25 mA**Times**

Switch-on delay typ. 5 s (after switching UBon)

Risk time according to EN 60947-5-3 max. 260 ms (Stand-alone device)

Delay time typ. 5 ms (Risk time delay....)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-CT-M-SEN-1-8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.