

INDUSTRIAL COMPONENT DATA

PSR-MC72-2NO-1DO-24DC-SC 2702096 PHOENIX CONTACT

Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-MC72-2NO-1DO-24DC-SC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-MC72-2NO-1DO-24DC-SC
Catalog number	2702096
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-CE9B69F44F
Generated	2026-08-06

Product Overview

Safety relays

Safety relay for emergency stop, safety doors, light barriers up to SIL 3, category 4, PL e, 1 or 2 channel operation, transverse short circuit detection, reactivatable, return/excitation delay of 0.2 s ... 60 s, 2 trip circuits, US = 24 V DC, plug-in screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2702096

Packing unit 1 pc

Catalog page Page 258 (C-6-2017)

GTIN 4046356952484

Weight per Piece (excluding packing) 108.980 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 12.5 mm

Height 112.2 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -35 °C ... 60 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Power supply

Rated control circuit supply voltage US 24 V DC -20 % / +25 %

19.2 V DC ... 30 V DC

Rated control supply current IS typ. 60 mA

Power consumption at US typ. 1.44 W

Inrush current typ. 25 A ($t = 10 \mu s$ at Us)

Filter time 10 ms (For the logic. At A1 in the event of voltage dips at Us)

Protective circuit Surge protection Suppressor diode

Protection against polarity reversal for rated control circuit supply voltage

Digital inputs

Input voltage range "0" signal 0 V DC ... 5 V DC (for safe Off)

Input current range "0" signal 0 mA ... 2 mA (for safe Off)

Inrush current < 11 mA (with Us/Ixto S12/S22)

< 8.6 mA (with Us/Ixto S34)

Current consumption < 4.1 mA (with Us/Ixto S12/S22)

< 3.2 mA (with Us/Ixto S34)

Filter time max. 3 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-MC72-2NO-1DO-24DC-SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.