

INDUSTRIAL COMPONENT DATA

PSR-ME40-4NO-2NC-24DC-SC-SET35 1397653 PHOENIX CONTACT Set of 35 safety relays as contact extension, adjustable deexcitation delay

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-ME40-4NO-2NC-24DC-SC-SET35



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-ME40-4NO-2NC-24DC-SC-SET35
Catalog number	1397653
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-3E867A3749
Generated	2026-08-05

Product Overview

Set of 35 safety relays as contact extension, adjustable deexcitation delay of 0.5 s ... 30 s, 4 enabling circuits, 1 feedback circuit, together with basic equipment up to category 3, PL d according to EN ISO 13849, plug-in screw terminal, width: 22.5 mm

Safety Relay

Set of 35 safety relays as contact extension, dropout delay can be set from 0.5 s ... 30 s, 4 enabling current paths, 1 confirmation current path, together with basic device up to Cat. 3, PL d in accordance with EN ISO 13849, plug-in screw terminal block, width: 22.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Technical dataProduct propertiesProduct type Safety relays

Product family PSRclassic

Application Extension module

Mechanical service life approx. 107cycles

Relay type Electromechanical relay with force-guided contacts in accordance with IEC/EN 61810-3

Times

Typical response time typ. 40 ms (For Usautostart)

Typical release time 50 ms (on demand via A1)

Delay time range 0.5 s ... 30 s $\pm 40\%$

Restart time < 1 s (Boot time)

Recovery time Delay time +500 ms

Electrical properties Maximum power dissipation for nominal condition 17 W (US= 26.4 V, $IL^2 = 72 A^2$, $P_{Total max} = 2.6 W + 14.4 W$)

Nominal operating mode 100% operating factor

Air clearances and creepage distances between the power circuits

Rated insulation voltage 250 V

Rated surge voltage/insulation See section "Insulation coordination"

Supply

Designation A1/A2

Rated control circuit supply voltage US 24 V DC -15% / $+10\%$

Rated control supply current IS typ. 77 mA (at US)

Power consumption at US typ. 1.85 W

Inrush current < 2.5 A (typically with US, $\tau_t = 1$ ms)

Filter time 5 ms (in the event of voltage dips at Us)

Protective circuit Reverse polarity protection; Suppressor diode

Input data Digital: K1/K2

Description of the input safety-related

Number of inputs 1

Input voltage range "0" signal 0 V DC ... 5 V DC

Input voltage range "1" signal 20.4 V ... 26.4 V

Input current range "0" signal 0 mA ... 2 mA

Filter time 1 ms (Test pulse width of low test pulses)

1 s (Test pulse rate for low test pulse)

No brightness test pulses / high t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-ME40-4NO-2NC-24DC-SC-SET35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.